## Control4® 8-Port Ethernet Switch



## Control4 8-Port Ethernet Switch (DIN Rail) (C4-DIN-8ESW-E)

The Control4 8-Port Ethernet Switch is a standard 8-port 10/100 switch that allows a single Ethernet CAT5e cable to be pulled into a lighting panel, and then distributed to up to seven other Control4 Centralized Lighting devices including Dimmer, Relay, and Bus Ethernet Bridge Modules within the panel.

- · Distributes an Ethernet connection up to seven other Control4 Centralized Lighting devices.
- Link/Activity LEDs indicate system link status and communication activity.
- · Power LED for power status.
- Reset button for rebooting the Ethernet switch without removing power.
- Line input for power.
- Can be installed in either a Control4 5-slot or 2-slot panel or a third-party DIN rail panel.

Model number	C4-DIN-8ESW-E
Power requirements	110V-277VAC, 50/60 Hz
Operating temperature	32°F to 104°F (0°C to 40°C)
Heat dissipation	7 BTU/hr @120VAC
Power consumption	2W
Communications	10/100 Ethernet
Connectors	Three screw terminals (Line, Neutral, Ground) One 26 AWG to 12 AWG (0.12 mm² - 4 mm²) per terminal Eight RJ-45 Ethernet
Humidity	5% - 95% non-condensing
Storage	-4°F ~ 158°F (-20°C ~ 70°C)
Dimensions (H×W×D)	8.5 × 4.3 × 2.3 in. (215 × 109 × 57 mm)
DIN module width	12M
Weight	2.3 lbs. (1.04 kg)
Shipping weight	2.8 lbs. (1.27 kg)



